



Adaptersats för att anpassa Regins ställdon till ventiler av andra fabrikat

ABS, VADSTENA, VM (Shuntmaster)

Artikel	Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
SV...25	SV...25	25 mm	20 mm	RVAN5...	OVA-131	195
SV...27	SV...27	25 mm	20 mm	RVAN5...	OVA-131	195
SV...33	SV...33	32 mm	20 mm	RVAN5...	OVA-131	195
SV...35	SV...35	32 mm	20 mm	RVAN5...	OVA-131	195
SV...36	SV...36	32 mm	20 mm	RVAN5...	OVA-131	195
SV...47	SV...47	40 mm	20 mm	RVAN5...	OVA-131	195
SV...54	SV...54	50 mm	40 mm	RVAN18...	OVA-031	202
SV...55	SV...55	50 mm	40 mm	RVAN18...	OVA-031	202
SV...56	SV...56	50 mm	40 mm	RVAN18...	OVA-031	202
SV...62	SV...62	65 mm	40 mm	RVAN18...	OVA-031	202
SV...65	SV...65	65 mm	40 mm	RVAN18...	OVA-031	202
SV...66	SV...66	65 mm	40 mm	RVAN18...	OVA-031	202
SV...67	SV...67	65 mm	40 mm	RVAN18...	OVA-031	202

ARI Armaturen

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
485-489	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-A1	286
485-489	65 – 100 mm	20 – 30 mm	RVAN18.../RVNA25...	OVA-A2	286
485-489	40 – 50 mm	14 mm	RVAN18	OVA-A3	246

Controlli

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
VSB	15 – 50 mm	16,5 mm	RVAN5.../RVAN10...	OVA-141	103
VMB	15 – 50 mm	16,5 mm	RVAN5.../RVAN10...	OVA-141	103

Danfoss

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
AB-QM	10 – 20 mm	2,3 mm	RVAPC...	N/A	-
AB-QM	25 – 32 mm	4,5 mm	RVAPC...	N/A	-

## ESBE

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
VL125	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL135	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL335	65 – 80 mm	20 mm	RVAN18.../RVAN25...	OVA-F4	65
VLA121	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLA221	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLA131	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLA325	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLA325	65 – 150 mm	40 mm	RVAN18.../RVAN25...	OVA-F4	65
VLB225	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLB225	65 – 150 mm	40 mm	RVAN18.../RVAN25...	OVA-F4	65
VLA335	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLA335	65 – 150 mm	40 mm	RVAN18.../RVAN25...	OVA-F4	65
VLB235	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLB235	65 – 150 mm	40 mm	RVAN18.../RVAN25...	OVA-F4	65
VLA425	25 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLE122	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLE132	15 – 50 mm	20 mm	RVAN.../RVAN10...	OVA-131	195
VLE222	25 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLE325	20 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLC125	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLC225	25 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLC325	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VLC425	25 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL2FC	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL3FC	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL2TA	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL2TAA	25 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL3TA	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL2FA	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL2FAA	25 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL3FA	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL2TB	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL2TBA	25 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL3TB	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL2FD	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
VL2FDA	25 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195

## Geomatic

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
V121G (M6 gängad spindel)	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-161	278

Honeywell

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
V5011R	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V5013A	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V5013F	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V5013R	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V5015A	100 – 150 mm	38 mm	RVAN18.../RVAN25...	OVA-013	679
V5329C	15 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V5329A	15 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V5016A	15 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V5016A	100 – 150 mm	38 mm	RVAN18.../RVAN25...	OVA-013	679
V5025A	15 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V5025A	100 – 150 mm	38 mm	RVAN18.../RVAN25...	OVA-013	679
V5049A	15 – 80	20 mm	RVAN5.../RVAN10...	OVA-011	450
V5049A	100 – 150	38 mm	RVAN18.../RVAN25...	OVA-013	679
V5050A	15 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V5050A	100 – 150 mm	38 mm	RVAN18.../RVAN25...	OVA-013	679
V5328A	15 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V176A	15 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V176B	20 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V176B	100 mm	38 mm	RVAN18.../RVAN25...	OVA-013	679
V538C6xxx	50 – 150 mm	27 – 40 mm	RVAN18.../RVAN25...	OVA-013	679
V538C3xxx	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V186	15 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V186	20 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-011	450
V186	100 mm	38 mm	RVAN18.../RVAN25...	OVA-013	679

Industrietechnik

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
VFX	15 – 20 mm (upp till Kvs 2,5)	2,5 mm	RVAPC...	N/A	-

## Johnson

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
VG7201/VG7203	25 – 32 mm	13 mm	RVAN5.../RVAN10...	OVA-J1	183
VG7201/VG7203	40 – 50 mm	19 mm	RVAN5.../RVAN10...	OVA-J1	183
VG7401/VG7403	25 – 32 mm	13 mm	RVAN5.../RVAN10...	OVA-J1	183
VG7401/VG7403	40 – 50 mm	19 mm	RVAN5.../RVAN10...	OVA-J1	183
VG7802/VG7804	25 – 32 mm	13 mm	RVAN5.../RVAN10...	OVA-J1	183
VG7802/VG7804	40 – 50 mm	19 mm	RVAN5.../RVAN10...	OVA-J1	183
BM-2xx2	15 – 50 mm	19 mm	RVAN5.../RVAN10...	OVA-J1	183
BM-2xx8	15 – 50 mm	19 mm	RVAN5.../RVAN10...	OVA-J1	183
VG6210	15 – 25 mm	2,5 mm	RVAPC...	N/A	-
VG6510	15 – 25 mm	2,5 mm	RVAPC...	N/A	-
VG6810	15 – 25 mm	2,5 mm	RVAPC...	N/A	-
V5210	10 – 20 mm	4 mm	RVAPC...	N/A	-
V5510	10 – 20 mm	3,7 mm	RVAPC...	N/A	-
V5810	10 – 20 mm	3,7 mm	RVAPC...	N/A	-



Adaptern OVA-J1 gäller för ventiler med M28x1,5 hals och ¼" UNF-28 gängad spindel.

## Kieback und Peter

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
RF	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-A1	286
RF	65 – 100 mm	20 – 30 mm	RVAN18.../RVAN25...	OVA-A2	286
RK	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-A1	286
RK	65 – 100 mm	20 – 30 mm	RVAN18.../RVAN25...	OVA-A2	286

## L&amp;G-, L&amp;S-, Siemens-ventiler

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
VFF33 (VARISHUNT)	65 mm	40 mm	RVAN18.../RVAN25...	OVA-031	202
VFF34 (VARISHUNT)	65 mm	40 mm	RVAN18.../RVAN25...	OVA-031	202
VFF35 (VARISHUNT)	65 mm	40 mm	RVAN18.../RVAN25...	OVA-031	202
VFF36 (VARISHUNT)	65 mm	40 mm	RVAN18.../RVAN25...	OVA-031	202
VFG33 (VARISHUNT)	25 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-134	295
VFG34 (VARISHUNT)	25 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-134	295
VFG35 (VARISHUNT)	25 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-134	295
VFG36 (VARISHUNT)	25 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-134	295
VPF52E	15 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VPF52F	15 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VVF21	15 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VVF21	100 mm	40 mm	RVAN18.../RVAN25...	OVA-082	90
VVF31	25 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VVF31	100 – 150 mm	40 mm	RVAN18.../RVAN25...	OVA-082	90
VVF40	15 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VVF40	100 – 150 mm	40 mm	RVAN18.../RVAN25...	OVA-082	90
VVF41	50 – 150 mm	20/40 mm	RVAN18.../RVAN25...	OVA-082	90
VVF45	50 – 150 mm	20/40 mm	RVAN18.../RVAN25...	OVA-082	90
VVF51/52	15 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VVF53	15- 50 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VVF61	15 – 25 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VVF61	40 – 150 mm	20/40 mm	RVAN18.../RVAN25...	OVA-082	90
VVG11 (VARIVALVE)	15 mm	5,5 mm	RVAZ4L1...	OVA-L1	25
VVG11	20 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-134	295
VVG12 (VARIVALVE)	25 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-134	295
VXF21	25 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VXF21	100 mm	40 mm	RVAN18.../RVAN25...	OVA-082	90
VXF31	25 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VXF31	100 – 150 mm	40 mm	RVAN18.../RVAN25...	OVA-082	90
VXF40	15 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VXF40	100 – 150 mm	10 mm	RVAN18.../RVAN25...	OVA-082	90
VXF41	15 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VXF41	50 – 150 mm	40 mm	RVAN18.../RVAN25...	OVA-082	90
VXF53	15- 50 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VXF61	15 – 25 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VXF61	40 – 150 mm	20/40 mm	RVAN18.../RVAN25...	OVA-082	90
VVG41	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VXG11 (VARIVALVE)	15 mm	5,5 mm	RVAZ4L1...	OVA-L1	25
VXG11	20 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-134	295
VXG12 (VARIVALVE)	25 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-134	295
VXG41	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-081	75
VXG44	15 – 50 mm	5,5 mm	RVAZ4L1	OVA-L1	25
VVG44	15 – 40 mm	5,5 mm	RVAZ4L1...	OVA-L1	25
VVG549	15 – 25 mm	5,5 mm	RVAZ4L1...	OVA-L1	25
VVI52	15 mm	5,5 mm	RVAZ4L1...	OVA-L1	25
VVG55	15 – 25 mm	5,5 mm	RVAZ4L1...	OVA-L1	25
VVP45	10 – 40 mm	5,5 mm	RVAZ4L1...	OVA-L1	25
VXP45	10 – 40 mm	5,5 mm	RVAZ4L1...	OVA-L1	25
VMP45	10 – 40 mm	5,5 mm	RVAZ4L1...	OVA-L1	25

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
VVI46	15 – 25 mm	2,5 mm	RVAPC...	N/A	-
VXI46	15 – 25 mm	2,5 mm	RVAPC...	N/A	-
VVS46	15 – 25 mm	2,5 mm	RVAPC...	N/A	-
VXS46	15 – 25 mm	2,5 mm	RVAPC...	N/A	-
VVP47	10 – 20 mm	2,5 mm	RVAPC...	N/A	-
VXP47	10 – 20 mm	2,5 mm	RVAPC...	N/A	-
VMP47	10 – 20 mm	2,5 mm	RVAPC...	N/A	-

## LDM

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
RV 111/T	15 – 40 mm	5,5 mm	RVAZ4L1...	OVA-L1	25
RV 111/W	15 – 40 mm	5,5 mm	RVAZ4L1...	OVA-L1	25
RV 111/F	15 – 40 mm	5,5 mm	RVAZ4L1...	OVA-L1	25

## Regin &amp; OSBY-ventiler (OAB)

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
2SAS, 2SBS, 2SAM, 2SBM	15 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-F1	135
2SBS, 2SBM	100 mm	38 mm	RVAN18...	OVA-F2	135
NTVS	15 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-F1	135
NTVS	100 – 150 mm	38, 40 mm	RVAN18.../RVAN25...	OVA-F2	135
CVFS	20 – 65 mm	32 mm	RVAN18...	OVA-F2	135
GTVS, GTRS	32 – 40 mm	20 mm	RVAN5.../RVAN10...	OVA-F1	135
GTVS, GTRS	50 – 150 mm	24 – 40 mm	RVAN18.../RVAN25...	OVA-F2	135
ETVS, ETVSU, ETRS, ETRSU	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-F1	135
FRS, FRSD	15 – 65 mm (kvs 0.6 – 6.3)	20 mm	RVAN5.../RVAN10...	OVA-F1	135
FRS	32 – 65 mm (kvs 10 – 20)	20 mm	RVAN18...	OVA-F2	135
MRT	20 – 25 mm	20 mm	RVAN5.../RVAN10...	OVA-F1	135
MTVS, MTRS	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-F1	135
STR, STV	15 – 50 mm	15 mm	RVAN5.../RVAN10...	OVA-121	85
MMV, MMR	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-134	295
BTV	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-F3 + 2921451401	-
BTR	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-F3	40
MMVA	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-F3	40
VTTV/VTTR/VTTB	15 – 20 mm (upp till Kvs 2,5)	2,5 mm	RVAPC...	N/A	-

## Gamla Osby-ventiler med 3/8" UNF-gänga på spindeln

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
2SA/2SB	15 – 80 mm	20 mm	RVAN5.../RVAN10...	OVA-132	295
2SB	100 mm	38 mm	RVAN18...	OVA-133	295
CVF	20 – 65 mm	32 mm	RVAN18...	OVA-133	295
GTR/GTV	25 – 50 mm	20 – 24 mm	RVAN5.../RVAN10...	OVA-132	295
GTR/GTV	65 – 150 mm	40 mm	RVAN18.../RVAN25...	OVA-133	295
MTR/MTV	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-132	295

Oventrop

Ventil	DN min.-max.	Slaglängd	Ställdon	Adapertyp	Pris
Cocon 2TZ	15 – 20 mm	2,5 mm	RVAPC...	N/A	-
Cocon QTZ	10 – 32 mm	2,8 / 3,5 / 4 mm	RVAPC...	N/A	-
Tri-M Plus	15 mm	2,5 mm	RVAPC...	N/A	-

Pettinaroli

Ventil	DN min.-max.	Slaglängd	Ställdon	Adapertyp	Pris
91-series	15 – 25 mm	3 mm	RVAPC...	VA7010	25
93-series	20 – 32 mm	6 mm	RVAPC...	VA748X	25

Riccus + Sohn

Ventil	DN min.-max.	Slaglängd	Ställdon	Adapertyp	Pris
RGV2	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-H1	183
RGV3	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-H1	183
HMVF2	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-H1	183
HMVF2	65 – 100 mm	20 – 30 mm	RVAN18.../RVAN25...	OVA-H2	183
HMVF3	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-H1	183
HMVF3	65 – 100 mm	20 – 30 mm	RVAN18.../RVAN25...	OVA-H2	183
RGVA2	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-A1	286
RGVA3	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-A1	286
HMVFA2	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-A1	286
HMVFA2	65 – 100 mm	20 – 30 mm	RVAN18.../RVAN25...	OVA-A2	286
HMVFA3	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-A1	286
HMVFA3	65 – 100 mm	20 – 30 mm	RVAN18.../RVAN25...	OVA-A2	286

Satchwell

Ventil	DN min.-max.	Slaglängd	Ställdon	Adapertyp	Pris
SVB-XXX-F3	50 – 150 mm	23 – 40 mm	RVAN18.../RVAN25...	OVA-133	295
SVG-XXX-F3	50 – 150 mm	23 – 40 mm	RVAN18.../RVAN25...	OVA-133	295
SVR-XXX-F3	50 – 150 mm	23 – 40 mm	RVAN18.../RVAN25...	OVA-133	295
SVR-G2	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-132	295
SVR-G3	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-132	295
VZ, MVZ	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-132	295
VZF, MVZF	65 – 150 mm	27 – 40 mm	RVAN18.../RVAN25...	OVA-133	295

## Sauter

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
V6R	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-151	795
B6R	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-151	795
VXD	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-151	795
VXE	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-151	795
BXD	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-151	795
BXE	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-151	795
V6F	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-151	795
V6G	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-151	795
V6S	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-151	795
B6F	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-151	795
B6G	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-151	795
B6S	15 – 50 mm	14 mm	RVAN5.../RVAN10...	OVA-151	795
VUL	10 – 20 mm	4 mm	RVAPC...	N/A	-
BUL	10 – 20 mm	3,7 mm	RVAPC...	N/A	-
VUT	10 – 20 mm	3/4 mm	RVAPC...	N/A	-
BUT	10 – 20 mm	3 mm	RVAPC...	N/A	-
VXL	10 – 20 mm	2,5 mm	RVAPC...	N/A	-
BXL	25 – 40 mm	2,9 mm	RVAPC...	N/A	-
VCL	10 – 32 mm	2,8 / 3,5 / 4 mm	RVAPC...	N/A	-



TAC + Schneider

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
STL	20 – 65 mm	31,5 mm	RVAN18...	OVA-031	202
STL-SR	20 – 65 mm	22 mm	RVAN5.../RVAN10...	OVA-131	195
V241	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V341	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V353	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V231	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V232	25 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V298	20 – 40 mm	22 mm	RVAN5.../RVAN10...	OVA-131	195
V211	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V211T	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V282	20 – 32 mm	22 mm	RVAN5.../RVAN10...	OVA-131	195
V282	40 – 50 mm	31,5 mm	RVAN18...	OVA-031	202
VG211	15 – 50 mm	16,5/25 mm	RVAN5.../RVAN10...	OVA-131	195
VG221F	65 mm	25 mm	RVAN10...	OVA-131	195
VG221F	80 – 150 mm	45 mm	RVAN18.../RVAN25...	OVA-031	202
VG222	65 – 150 mm	25/45 mm	RVAN18.../RVAN25...	OVA-031	202
VG321	65 – 150 mm	25 – 45 mm	RVAN18.../RVAN25...	OVA-031	202
V311	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V311T	15 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V212	25 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V212T	25 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V395	40 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V395	65 – 100 mm	30/39,5 mm	RVAN18.../RVAN25...	OVA-031	202
V265	40 – 100 mm	31,5/40,9/50,3 mm	RVAN18.../RVAN25...	OVA-031	202
V221	65 – 100 mm	30/39,5 mm	RVAN18.../RVAN25...	OVA-031	202
V384	20 – 32 mm	22 mm	RVAN5.../RVAN10...	OVA-131	195
V384	40 – 50 mm	31,5 mm	RVAN18...	OVA-031	202
V386	20 – 32 mm	22 mm	RVAN5.../RVAN10...	OVA-131	195
V386	40 – 50 mm	31,5 mm	RVAN18...	OVA-031	202
V392	20 – 32 mm	22 mm	RVAN5.../RVAN10...	OVA-131	195
V392	40 – 50 mm	31,5 mm	RVAN18...	OVA-031	202
V394	20 – 50 mm	20 mm	RVAN5.../RVAN10...	OVA-131	195
V292	20 – 32 mm	22 mm	RVAN5.../RVAN10...	OVA-131	195
V292	40 – 100 mm	31,5/40,9/50,3 mm	RVAN18.../RVAN25...	OVA-031	202
V294	20 – 32 mm	22 mm	RVAN5.../RVAN10...	OVA-131	195
V295	20 – 32 mm	22 mm	RVAN5.../RVAN10...	OVA-131	195
V295	40 – 100 mm	31,5/40,9/50,3 mm	RVAN18.../RVAN25...	OVA-031	202
V222	65 – 100 mm	30 mm	RVAN18...	OVA-031	202
V321	65 – 100 mm	30 mm	RVAN18...	OVA-031	202
VZ28/VZ28C	15 – 20 mm	2,5 mm	RVAPC...	N/A	-
VZ38/VZ38C	15 – 20 mm	2,5 mm	RVAPC...	N/A	-
VZ48/VZ48C	15 – 20 mm	2,5 mm	RVAPC...	N/A	-

Watts Industries

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
2131	15 – 25 mm	2,5 mm	RVAPC...	N/A	-
3131	15 – 25 mm	2,5 mm	RVAPC...	N/A	-
4131	15 – 25 mm	2,5 mm	RVAPC...	N/A	-

## WSE/Norshunt

Ventil	DN min.-max.	Slaglängd	Ställdon	Adaptertyp	Pris
FM25	25 mm	23,5 mm	RVAN5.../RVAN10...	OVA-FM25	350
FM50	50 mm	37,5 mm	RVAN18...	OVA-FM50	350

