

## Exempel 001

Funktionsbeskrivning: Blandad värmekrets 1 (kontinuerlig)



	G				
	G0				P1 B
	Gnd				P1 A
	+C				P1 N
	Gdo				P1 E
VS1 pump A	DO1	10	G <sub>DO</sub>		P2 B
	DO2	11	DO1		P2 A
	DO3	12	DO2		P2 N
	DO4	13	DO3		P2 E
	DO5	14	DO4		
	DO6	15	DO5		Ext D
	DO7	16	DO6		
	Agnd	17	DO7		DI1
		30	Agnd		DI2
Utetemperatur	AI1	31	AI1		DI3
VS1 framledningstemp	AI2	32	AI2		DI4
	Agnd	33	Agnd		DI5
	AI3	34	AI3		DI6
	AI4	35	AI4		DI7
		40	Agnd		DI8
	Agnd	41	UI1 :AI5/DI9		Agnd
	UI1	42	UI2 :AI6/DI10		AO1 VS1 Ventil
	UI2	43	Agnd		AO2
	Agnd	44	UI3 :AI7/DI11		AO3
	UI3	45	UI4 :AI8/DI12		AO4
	UI4				AO5
	TCP				

Plintanslutningar

Tillgänglig för: HCA152W-4, HCA152DW-4, HCA282DW-4, HCA283WM-4, HCA283DWM-4

Application tool-fil: 001\_HCAxxxxx\_HSco