



TG-DHW1/NTC1.8

Immersion sensor with well and housing.

Temperature sensor with NTC 1.8 element for water temperature measurement.

- Anti-tear M16 cable gland
- Screw cap
- R1/2" connection

- Well and probe in stainless steel
- Modern design and compact format
- Simple and quick installation

Tempero series immersion sensor with a modern design suiting all environments. The sensor part has a snap-on fastening for the well, making it easy to mount.

Comes supplied with a DR-90WS model well. The sensor is compatible with TAC.

Technical data

Temperature range	-20...+120°C
Compatible with	TAC
Sensor element	NTC 1.8, 1800 Ω/25°C
Time constant	18 s (12 s with heat-conductive paste)
Cable gland	M16
Insertion length, well	90 mm
Diameter, probe	5 mm
Diameter, well	8 mm
Connection	R1/2"
Pressure rating	PN25
Protection class	IP65

Material

Housing	Polycarbonate
Probe and well	Stainless steel, SUS304


Colour

Cover	Polar white RAL9010
Base	Dark grey RAL7043

Temperature (°C)	Resistance (Ω)
35	1250
30	1496
25	1800
20	2177
15	2649
10	3241
5	3989
0	4940
-5	6159
-10	7730
-15	9771
-20	12443

Temperature (°C)	Resistance (Ω)
120	110
110	139
100	178
90	230
80	303
70	403
65	468
60	545
55	638
50	750
45	885
40	1049

Dimensions (mm)



Head office Sweden

Phone: +46 31 720 02 00

Web: www.regincontrols.com

Mail: info@regin.se

REGIN

THE CHALLENGER IN BUILDING AUTOMATION