

VALVES APPLICATION

DZR* Requirement
District heating
Heating / Cooling / Ventilation
Chilled beams, ceilings etc.
Fan-coil



VALVE	TYPE	NOMINAL DIAMETER	KVS	STROKE	PN	CONNECTION					
CTV	2-way	DN10-15	0,12-1,9	3,5 mm	10	External thread					
ZFCM	2- & 3-way	DN15-32	3,2-10	20°	16	Internal threads					



VTTV	2-way	DN15-20	0,25-6	2,5 mm	16	External threads					
VTTR	3-way										
VTTB	3-way with bypass										



ZTV	2-way	DN15-25	0,25-7	5,5 mm	16	External threads					
ZTR	3-way										
ZMD	2- & 3-way	DN15-40	0,25-25			External thread (internally threaded unions included)					



ETVS	2-way	DN15-50	0,25-40	20 mm	16	External thread (internally threaded unions included)					
ETRS ¹	3-way										
MTVS	2-way		0,63-39			Internal threads					
MTRS	3-way										
BF	2- & 3-way		0,63-40								
BTV	2-way		0,6-39								
BV	2- & 3-way		0,60-63	90°	40						
BVH	2- & 3-way		4,0-63		20						



PCTVS	2-way PICV Pressure independent control valve	DN15	150–900l/h	2,7 mm	25	Internal threads					
PCTVS		DN20				External threads					
PCMTV		DN15–25	150–1500l/h			6 mm	Internal threads				
		DN20–32	2200–3000l/h	External thread (internally threaded unions included)							
		DN32–50	6000–18000l/h		90°	40	Flanged				
		DN50–250	25700–277000l/h	Multi-turns							



GFH	2-way/3-way	DN15-50	2,5-40	14 mm	16	Flanged					
GFH	2-way/3-way	D65-100	50-160	30 mm	16	Flanged					
GFH	2-way/3-way	D125-150	250-315	50 mm	16	Flanged					

After selecting valve with this quick guide, please check product sheet to make sure you have chosen correctly according to differential pressure etc.

¹ Can be used as 2-way valve as well with the attached blind cover

* DZR = Dezincification Resistant

DZR* Requirement
District heating
Heating / Cooling / Ventilation
Chilled beams, ceilings etc.
Fan-coil