XF193TM-1 MVD_Envdecl.doc

Page 1 of 4

Created: 2003-03-02 Printed: 2015-11-30

Environmental declaration Type II

GENERAL PRODUCT INFORMATION

Name of product seriesPackagingXF193TM-1Cardboard

COMPANY INFORMATION

Company, address and telephone

AB REGIN Box 116 SE-428 22 Kållered

Sweden

Tel: +46 - (0)31 - 720 02 00 Fax: +46 - (0)31 - 94 01 46

E-mail:

Company description

Regin is the collected trademark for products and systems in building automation. The company's knowledge is based on many years of wide experience in control, automation and flow control. AB Regin has a certified quality assurance system according to ISO 9001.

Ongoing environmental work

Regin designs products on commission from clients as well as for resale. Regin has no production of its own and has thereby no product related consequences for the environment. Regin can control environmental aspects related to product development and when choosing suppliers and components. AB Regin intend to begin working with environmental certification according to ISO 14 001. AB Regin intend to gradually start developing MVD Type II (Regin's own environmental declaration) for our products.

XF193TM-1 MVD_Envdecl.doc

Page 2 of 4

Created: 2003-03-02 Printed: 2015-11-30

PRODUCT INFORMATION

General

The recommended field of application is stated in the technical documentation.

There is an unambiguous and lasting label (manufacturer, product name, serial number etc) on the product.

The labelling is linked to the technical documentation which makes the product clearly identifiable.

Product design

XF193TM-I Is an electronic controller solution with 3 main parts. The enclosure has a front, middle and a back cover where UI is in the front cover. Enclosed in the middle part are the two PCB with components and display module which attached to the back side of the front cover. In the bottom cover are all the cable connection terminals located.

Component modules	Weight grams	Weight %
Enclosure	202	48
Electronics	163	38
Terminals	34	8
Earth connectors	21	5
Earth cable	3	I

PRODUCT INCORMATION DECOURGES AND HAZARDOUG SURSTANCES			
PRODUCT INFORMATION, RESOURCES AND HAZARDOUS SUBSTANCES Resources Hazardous			
Component modules	(metals, organic, non-organic substances)	substances (Kd, Hg, Pb, PCB, PVC, PBB, PBBE etc)	
PCB	Epoxi, Cu, Ag; TBBP-A	TBBP-A	
Casing	PC		
CR2032	Lithium		
Terminals	Fe, Brass, Sn, PA66		
Buttons	Rubber		
Earth connectors	Fe, Sn		
Notes, the product's content			

Battery included in XFI93TM-1.



XF193TM-1 MVD_Envdecl.doc Page 3 of 4

Created: 2003-03-02 Printed: 2015-11-30

PRODUCTION

Regin has no production of its own and has therefore no product related environmental policy. The components are mounted manually and are thereafter soldered together with classified soldering. The environmental consequences are negligible, and consist solely of air outlet from soldering The operation does not require licencing

DISTRIBUTION

Production origin Hultsfred, Sweden Mode of transportation Lorry, train

Mode of distribution The product is normally distributed via a warehouse/wholesaler.

Wrapping Material Wood, paper, plastic

Packaging material can not be returned. AB Regin is connected to REPA.

BUILDING PHASE

Documented instructions for mounting and commissioning are included with the product.

The instructions contain recommendations concerning

- Safeguard measurement for handling procedures and mounting.
- Handling of the product at the workplace and during mounting.

USAGE PHASE

Normal operation

The product requires energy (electricity) during normal operation. Power consumption approx. 10 VA.

The product does not have any environmental impact on the surrounding environment during normal operation.

Normally, the product does not require any maintenance.

It is possible to estimate the product's life span in advance.

There is no documentation concerning the expected life span when the product is under different conditions.

Documented instructions for appropriate operation and maintenance are supplied with the product.

Emergency

In case of fire the plastic may emit gases harmful to human health. The amounts of these substances are small compared with the size of the product.

Circuit boards may emit toxic flue gases.

DEMOLITION

The product is prepared for environmental-friendly dismantling. Dismantling of the product:

- 1. Split apart the enclosure to remove PCB remove the battery and sort in as electronic waste.
- 2. Separate battery, plastic components, electronic components and recycle at appropriate facility.



XF193TM-1 MVD_Envdecl.doc

Page 4 of 4

Created: 2003-03-02 Printed: 2015-11-30

WASTE MANAGEMENT

The long life span of the product means that the recycling situation may differ from today when the product is recycled.

The product is required, by law, to be handled according to standard waste management procedures. The materials can easily be separated to a high separation degree.

Plastic parts can, theoretically, be recycled. Recovering of energy through combustion is considered the best option in the present situation, since the plastic does not contain any substances dangerous to the environment.

Circuit boards with components are required by law to be dismantled and constituent components to be identified. Swedish companies in electronic recycling separate in three main fractions. Recycling of materials, recovering of energy and dangerous waste.

Identified metallic constituents are returned to metal recycling.

Combustible materials are returned for safe disposal in a licenced incinerator.

Dangerous waste is returned for destruction to a licenced entrepreneur.

