



RVAPC-230

230V AC valve actuator for 3-position control

RVAPC-230 is a valve actuator for control of Regin's pressure independent valves PCTV/PCMTV/PCTVS DN15-32.

The RVAPC-230 valve actuator is intended for use in HVAC applications together with Regin's pressure independent valves PCTV, PCMTV and PCTVS DN15-32.

The actuator is compact, easy to install and has a LED indicator which shows the status and diagnostic of the actuator.

Small and compact for easy installation and maintenance

The compact design of the RVAPC-230 actuator makes it suitable for installation in confined spaces, such as fan coils, chilled ceiling manifolds, etc. The cable is removable to simplify connection and replacement.

Clear operating status indication

RVAPC-230 features a green LED indicating operating status.

Short facts about RVAPC-230

- Small and compact with removable cable for easy installation and maintenance
- Clear operating status indication

Technical data

Supply voltage	230 V AC \pm 10 %
Control signal	3-position
Power consumption	6.5 VA
Max. stroke	6 mm
Stroke time	8 s/mm
Force	120 N
Ambient temperature	0...50°C
Max. media temperature	95°C
Storage temperature	-20...+65°C
Ambient humidity	Max. 95 % RH
Protection class	IP43


Adapters (must be ordered separately)

for valves with 2.7 mm stroke	VA7010
for valves with 6 mm stroke	VA748X




This product carries the CE-mark. More information is available at www.regincontrols.com.

Wiring



Dimensions



Product documentation

Document	Type
Product sheet PCTV/PCMTV/ PCTVS15-25	Information about pressure independent valves intended for use together with RVAPC-230
Product sheet PCMTV25-32	Information about pressure independent valves intended for use together with RVAPC-230
Instruction RVAPC-230	Instruction for RVAPC-230

The documents can be downloaded from www.regincontrols.com

Head Office Sweden

Phone: +46 31 720 02 00
 Web: www.regincontrols.com
 Mail: info@regin.se